

FY-GL-HB I -546W



FEATURES

- IP65 waterproof design.
- High efficacy up to 2.3 $\mu\text{mol}/\text{J}$.
- Fanless design, no noise.
- 100-277 V wide input voltage.
- 2 channels Dimmable control separately.
- Suspension, surface and Flush Mounting Options.
- Full spectrum 12 bands for VEG to bloom, full growing stages.
- Unmatched Hanging Versatility.
- 5 years warranty.
- Available in 600mm-2ft,1200mm-4ft,1500mm-5ft

CERTIFICATES

DLC / UL / CUL / CE / RoHS

WARRANTY

Default is 3 years. 5 years warranty is optional

APPLICATIONS

- Home hobbyist
- Agricultural universities
- Educational programs in local school districts
- Plant physiological research
- Biotechnology
- Pharmacology
- Greenhouses
- Plant factories




SPECIFICATION


Model	FY-GL-HB I-546W
Spectrum	Full Spectrum
Input Voltage	AC 100-277 V, 50 / 60 HZ
Power Factor	>0.95
Dimming	0-10 V
Dimension	59" x 5.9" x 2.7" L 1500 * W 150* H 70 mm
LED Quantity	0.5 w * 1092=546W
Rated Power	546 W
Draw Power	360 W
PPF	828 $\mu\text{mol}/\text{s}$

Efficacy	2.3 $\mu\text{mol}/\text{J}$
IP Rating	IP65
Beam Angle	120°
Operating Temperature	-4 - 104 °F / (-20 - 40 °C)
Lifetime	Q (L)90: 68, 300 hours
Certificates	DLC, cULus, CE, RoHS, Damp Location Rated
Warranty	5 years
Master carton (1PC/CTN)	1555 * 195 * 165 mm
Gross Weight	10.5 KG/PC
Volume weight	10 .6KG/PC

SPECTRUM



A1



A3

ACCESSORIES




ADJUSTABLE STAINLESS STEEL
HANGING KITS -1SET



OPTIONAL HANGING KITS



ROTATABLE SURFACE
MOUNTING BRACKETS





OPTIONAL MOUNTING BRACKETS
(DOUBLE LIGHTS IN A LINE)



OPTIONAL MOUNTING BRACKETS
(THREE LIGHTS IN A LINE)

DIMENSIONS



PACKING INFORMATION

G.W.of inner carton	Size of inner box	Size of master carton	Quantity of master carton	G.W.of master carton	Storage temperature
BLANK	BLANK	1555 * 195 * 165 mm	1 pc	10.5 kgs	-40°C~80°C